

76IIH Parameter

Printing	
Printing method	9-Pin serial impact dot-matrix printing
Printing width	63.5 mm
Column capacity	400 dots/line
Printing speed	4.5 line/s Max.
Interface	USB / USB+Lan
Printing paper	75.5±0.5mm×φ80mm(max)
Line spacing	4.23mm (Adjustable by commands)
Character size	ANK, Font A: 1.6×3.1mm (9×9 dots) Font B: 1.2×3.1mm (7×9 dots) Chinese,traditional Chinese: 2.7×2.7mm (16×16 dots)
Column number	76mm paper: Font A - 32 columns /Font B - 42 columns / Chinese,traditional Chinese - 22 columns
Character	
Extension character sheet	PC347、Katakana、PC850、PC860、PC863、PC865WPC1252、PC866、PC852、PC858
Power	
Power adaptor	Input: AC 110V/220V, 50~60Hz
Power source	Output: DC 24V/2.5A
Cash drawer output	DC 24V/1A
Cutter	
Auto cutter	NONE
Physical characteristics	
Gross weight	1.46 KG
Dimensions	230×150×138mm (D×W×H)
Environmental Requirements	
Work environment	0~45℃, 10~80% RH
Storage environment	-10~60℃, 10~90% RH (no condensation)
Reliability	
Cutter life	1 million cuts
Printer head life	10 million lines